

## Certificate of Registration

**Certificate Number 645**

Placed on the Market under the Name of

**Hanson and Beards Ltd  
Holmfield Industrial Estate  
Holmfield  
Halifax  
HX2 9TN  
United Kingdom**

and produced in the manufacturing plant

**Hanson & Beards Ltd, Holmfield Industrial Estate, Holmfield, Halifax, HX2 9NT, United Kingdom**


This certificate attests that all provisions have been met concerning the BM TRADA requirements of the scheme:

**Q-Mark Timber Fire Door Manufacture**

Date of Initial Certification: **04/12/2012**

Date of Last Issue: **31/10/2024**

Date of Expiry: **04/10/2027**



**Jon Lessimore (Divisional Director)**  
For and on behalf of Element

## Scope of Certification

### Primary Field of Application (FoA) Reports (owned by this certified company)

Either used in isolation, or can be used in conjunction with an appropriate associated document for this company, providing that the FoA report allows it and that both documents are compatible with each other. Where more than one primary FoA is listed for the same doorset type, they cannot be mix and matched, only one FoA is to be chosen and followed precisely

Type	FoA Report	Rev	Owned by Certified Company named on this scope	Doorset Description	Integrity Period	FoA Standard
Fire	Chilt/A13211	B	Hanson & Beards Limited	Anodoor 44 (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-	-			N/A
Fire	Chilt/A13218	C	Hanson & Beards Limited	Anodoor 54 (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-	-			N/A
Fire	WF391096	-	Hanson & Beards Limited	Anodoor 44 Ultra (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-	-			N/A
Fire	WF400733	-	Hanson & Beards Limited	Anodoor 54 Ultra (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-	-			N/A
Fire	WF510557	-	Hanson & Beards Limited	Anosecure (Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-	-			N/A

### Primary Field of Application (FoA) Reports (owned by and cascaded by a System Supplier)

The revision status of each FoA can be verified on the BM TRADA website under each System Supplier's certification entry. They are either used in isolation, or can be used in conjunction with an appropriate associated document for this company, providing that the FoA report allows it and that both documents are compatible with each other. Where more than one primary FoA is listed for the same doorset type, they cannot be mix and matched, only one FoA is to be chosen and followed precisely.

Type	FoA Report	System Supplier owner of Assessment Report	Doorset Description	Integrity Period	FoA Standard
Fire	Chilt/A13085	Egger UK Limited	Egger FD30 and FD30 Décor 44mm Door Blanks (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A01204	Halspan Limited	Optima 30 Part 1 Timber (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A01205	Halspan Limited	Optima 60 (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	FEA/F97174	Halspan Limited	Prima 30 Part 1 Timber (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	FEA/F96103	Halspan Limited	Prima 60 Part 1 Timber (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	FEA/F97097	Halspan Limited	Optima and Prima 30 Panelled (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A01015	Halspan Limited	Prima 60 Panelled (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A05151	Halspan Limited	Halspan 90 (Glazed or Unglazed)	90min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	BMT/CNA/F15082	Halspan Limited	Halspan 120 (Glazed or Unglazed)	120min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A02066	Falcon Timber Limited	STREbord® 44 door assemblies for 30 Minutes Fire Resistance (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A02067	Falcon Timber Limited	STREbord® 54 doorsets for 60 Minutes Fire Resistance (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A10152	Falcon Timber Limited	STREbord® 54 Panelled Range of Doorsets using STREbord® 54 Panelled Door Blanks in Timber Based Door Frames 60 Minutes Fire Resistance (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	FEA/F98164	Pacific Rim Wood Ltd	Flamebreak Doorsets for 30 minutes Fire Resistance (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	FEA/F02141	Pacific Rim Wood Ltd	Flamebreak 660 and FF660 Doorsets for 60 minutes Fire Resistance (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A13058	Moralt AG	LAMINESSE FireSmoke Only 44/54mm (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A13059	Moralt AG	LAMINESSE FireSmoke 54mm Only (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	BMT/CNA/F14274	Moralt AG	LAMINESSE FireSound 44mm (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	WF409922	Moralt AG	LAMINESSE FireSound 54mm (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	WF409922	Moralt AG	LAMINESSE FireSound 54mm (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	WF409922	Moralt AG	LAMINESSE FireSound 59mm (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	WF409922	Moralt AG	LAMINESSE FireSound 59mm (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	BMT/CNA/F15084	Winkhaus UK Ltd	Winkhaus Timber Frame with Halspan Blank (Glazed or Unglazed)	30min	EN 1634-1
Smoke	N/A	-			N/A
Fire	BMT/CNA/F15084	Winkhaus UK Ltd	Winkhaus Timber Frame with Halspan Blank (Unglazed only)	60min	EN 1634-1
Smoke	N/A	-			N/A
Fire	BMT/CNA/F15057	Sealed Tight Solutions Ltd	STS Leaf Edge Seals for Falcon 54mm Doorsets	60min	BS 476 Pt22
Smoke	N/A	-			N/A

### Test Reports

Test reports cannot be used in conjunction with any primary FoA reports, other test reports or associated documents. They must be followed precisely without any deviation whatsoever.

No specification or parameter changes are allowed at all from that stated within the test report such as size, shape, design, glazing, leaf/frame specification, hardware etc.

Type	Test Report	Owner of Test Report	Doorset Description	Integrity Period	Test Standard
Fire only	WF405276	Hanson & Beards Limited	Strebord 44 (Unglazed)	30min	BS 476 Pt22